



Quality that you can touch, the island range from MKN

Design award winner

Optional accessories

1.	Top plate corner version 45°	Only with top plate projection
2.	Top plate corner version radius R50	Only with top plate projection
	Continuous rear wall panelling For several appliances	Only with top plate projection
3.	Top plate utensils box 2 x 1/3 GN (without GN containers)	Only in connection with OPTIMA worktable
4.	Round handrail, 50 mm in diameter	Only with top plate projection

1.




Top plate, 45° corner version

2.



Top plate, 50° corner version

3.



Top plate utensils box

4.



Handrail

For further optional accessories please refer to “optional accessories for Optima production lines”

on page 103. Some of the photos show models with several optional extras.

Quality that you can touch, the island range from MKN

Design award winner

Calculation example*

OPTIMA 850	Standard model	OptimaMeister 850
€ 5000,—	Electric deep fat fryer	€ 5000,—
€ 4000,—	Electric griddle plate Width 600 mm	€ 4000,—
€ 7000,—	Gas range with electric oven, Width 800 mm	€ 7000,—
€ 100,—	connection profiles	
	Seamless continuous top plate	€ 2000,—
€ 16100,—		€ 18000,—

* detailed OptimaMeister calculation on request

Important planning details:

- ◆ Solid top ranges only in appliance length 1000mm (for thermal effect reasons). Additional charge to standard appliance
- ◆ In gas ranges with oven the substructure on the right next to the oven must be free for maintenance purposes.
- ◆ In versions B + C, the top plate width is calculated by the corpus length + 100 mm (top plate projections)
- ◆ In version C (free-standing model) the substructure is open on both sides. Continuous rear wall panelling in the substructures for several appliances (refer to optional accessories).
- ◆ Please consult us before planning electric quick boiling kettles